

Plus Series 275 Single Hung/375 Single Slider

Windows for Life™



2015 2014



ENERGY STAR
HIGH EFFICIENCY
HAUTE EFFICACITÉ

Sustained Excellence



ENERGY STAR
HIGH EFFICIENCY
HAUTE EFFICACITÉ

Promoter of the Year
ENERGY STAR Most Efficient



ENERGY STAR
PARTICIPANT



9 consecutive years
2006 - 2015



"You'll appreciate the quality we build into every window!"



frame **THE VINYL COMPANY**
QUALITY EXTRUDERS SINCE 1998

glass Stainless


The TempSmart[™] Spacer System

IGMA INSULATING GLASS MANUFACTURE ASSOCIATION

VERSATILE & FLEXIBLE

For new homes, these windows are built to your individual needs with optional nailing fin and brick mould, with jamb returns and frame extensions to fit your type of wall construction.

- **Fusion Welded 2 3/4" Frame and Sash**
Welding creates a fully sealed, continuous profile that eliminates potential air and water penetration through frame and sash corners.
- **Maintenance Free Solid uPVC Vinyl Profiles**
The multi-chambered design provides structural strength as well as insulating air pockets which reduce heat and cold transfer.
- **Integral Pull Rail**
Permits sashes to be operated with ease.
- **Large Interlock with Double Protection**
Brings double weatherstrip sashes closer together and locks them air tight for another secure line of defense against the weather.
- **Built-in Water Management Systems**
Carefully engineered independent water management system allows for quick drainage to the exterior.
- **Integral Nail Fin Option**
275NF and 375NF versions contain an integrated Nail Fin which is ideal for siding applications utilizing a standard siding J.



Window Ratings 275

Tested to: AAMA/WDMA/CSA101/LS.2/A440-08&11 + CSA A440 S1-09 R-PG35 DP 1680pa Water Penetration Resistance 330pa A3 Grade 10

Window Ratings 375

Tested to: AAMA/WDMA/CSA101/LS.2/A440-08&11 + CSA A440 S1-09 R-PG30 DP 1680pa Water Penetration Resistance 220pa A2 Grade 10 Energy Rating (as high as): +32 double glazed U value (as low as) 0.28(1.59) double glazed* CSA Certified NFRC Certified • ENERGY STAR Qualified USA ENERGY STAR 2016 U.30 SHGC .57

Single Hung

Style 275/275NF

Width: Min 12" Max 36"
Height: Min 22" Max 72"

Single Slider Vent Slider

Style 375/375NF

Width: Min 22" Max 72"
Height: Min 12" Max 36"

Double End

Style 375EV/375EVNF

Width: Min 42" Max 96"
Height: Min 12" Max 36"

**Widths less than 56" must be 1/3, 1/3, 1/3*

** Tested with Low E, Argon Gas and a warm edge spacer *Ask your dealer for details of glass requirements.*

- **Commercial Glazing Technique**
Exterior glass stops combined with our wet glazing technique provide the ultimate defense against air and water penetration, with long lasting beauty.
- **High Performance Glass**
Choose Solar Gain Low E for free solar heat or Solar Shield Low E for reducing solar heat gain. Argon and Krypton Gas fillings will maximize heat savings!
- **3/4" Overall Insulating Glass**
Results in superior thermal performance.
- **Warm Edge Spacer Technology**
Only the best warm edge spacers will reduce perimeter condensation on an insulating glass unit, fight mold and increase the comfort of your home.
- **IGMA(IGCC) Approved**
Certification Numbers - Stainless #2521, TempSmart[™] #2248

hardware



- **Weatherstrip For Results**
Premium quality fin seal is the ideal weather resistant design for sliders.
- **Recessed Tilt Latches**
Your operating sash tilts in for easy cleaning from inside your home. Our recessed design maintains a clean and attractive sight line in your window.
- **Quick Release Coil Balance**
Effortless sash movement with simple sash removal.
- **Quick Lock Shoes**
When you tilt your sash for cleaning, an immediate locking action from multi-directional shoe expansion break-points secures the sash in place.
- **Screen**
Roll form aluminum half screen with fiberglass mesh fits snugly inside the frame.
- **Hinged Drain Covers**
Built in flaps let water out and close tightly to resist air infiltration and insect penetration.

As we are constantly improving our products, specifications may have changed from those herein. Please contact WVD regarding up-to-date specifications.




Wide Selection of Styles and Configurations




Optional Internal grills for beauty and distinction.

Style 275/275NF



Style 375/375NF



Style 375EV/375EVNF



Authorized Distributor

