



Premium & Plus Series 150 Awning



MODEL	PRODUCT NAME	STYLE	U-FACTOR (W/m ² - K)	SOLAR HEAT GAIN (SHGC)	ENERGY RATING	FRAME MATERIAL	LAYERS OF GLAZING	NRCan REFERENCE	ENERGY EFFICIENCY VERIFICATION REFERENCE	U-FACTOR (BTU/H/FT ² - °F)	VISIBLE TRANSMITTANCE	AIR LEAKAGE - INFILTRATION (L/S*M ²)	AIR LEAKAGE - EXFILTRATION (L/S*M ²)
150-CL-AIR-CL-ARG-PLANILUX-IU	150 Awning	Awning (single)	1.31	0.42	35	Vinyl	3	NR5742-21417380-ES5	VID-N-2-00063-00001	0.23	0.49	0.1	0.1
150-CL-AIR-CL-ARG-PLANILUX-SS	150 Awning	Awning (single)	1.25	0.42	37	Vinyl	3	NR5742-21417382-ES5	VID-N-2-00064-00001	0.22	0.49	0.1	0.1
150-CL-AIR-CL-ARG-PLANILUX-SS-GRL	150 Awning	Awning (single)	1.25	0.38	34	Vinyl	3	NR5742-21417383-ES5	VID-N-2-00064-00002	0.22	0.44	0.1	0.1
150-CL-ARG-PLANILUX-ARG-PLANILUX-IU	150 Awning	Awning (single)	1.08	0.41	40	Vinyl	3	NR5742-21417384-ES5	VID-N-2-00065-00001	0.19	0.48	0.1	0.1
150-CL-ARG-PLANILUX-ARG-PLANILUX-IU-GRL	150 Awning	Awning (single)	1.08	0.37	38	Vinyl	3	NR5742-21417385-ES5	VID-N-2-00065-00002	0.19	0.43	0.1	0.1
150-CL-ARG-PLANILUX-ARG-PLANILUX-SS	150 Awning	Awning (single)	1.08	0.41	40	Vinyl	3	NR5742-21417386-ES5	VID-N-2-00066-00001	0.19	0.48	0.1	0.1
150-CL-ARG-PLANILUX-ARG-PLANILUX-SS-GRL	150 Awning	Awning (single)	1.08	0.37	38	Vinyl	3	NR5742-21417387-ES5	VID-N-2-00066-00002	0.19	0.43	0.1	0.1
150-SB60-ARG-SB60-ARG-CL-IU	150 Awning	Awning (single)	1.02	0.22	30	Vinyl	3	NR5742-21417376-ES5	VID-N-2-00061-00001	0.18	0.39	0.1	0.1
150-SB60-ARG-SB60-ARG-CL-IU-GRL	150 Awning	Awning (single)	1.02	0.2	29	Vinyl	3	NR5742-21417377-ES5	VID-N-2-00061-00002	0.18	0.35	0.1	0.1
150-SB60-ARG-SB60-ARG-CL-SS	150 Awning	Awning (single)	1.02	0.22	30	Vinyl	3	NR5742-21417378-ES5	VID-N-2-00062-00001	0.18	0.39	0.1	0.1
150-SB60-ARG-SB60-ARG-CL-SS-GRL	150 Awning	Awning (single)	1.02	0.2	29	Vinyl	3	NR5742-21417379-ES5	VID-N-2-00062-00002	0.18	0.35	0.1	0.1

Notes: PlanLux = Solar Gain | SB60 = Solar Shield | iu= Stainless Spacer | ss= Super Space | GRL = Grills