



"You'll appreciate the quality we build into every window!"





rame

THE VINYL COMPANY

VERSATILE & FLEXIBLE

your individual needs

Fusion Welded Frame and Sash

Welding creates a fully sealed, continuous profile that eliminates potential air and water penetration through frame and sash corners.

Maintenance Free Solid uPVC Vinyl Profiles

The multi-chambered design provides structural strength as well as insulating air pockets which reduce heat and cold transfer.

· Integral Pull Rail

Permits the single sash to be operated with ease.

· Built-in Water Management Systems

Carefully engineered independent drain allows for quick water management to the exterior.

· Integral Brick Mould with Nail Fin

Ideal for brick and siding applications, offering cleaner details and improved performance (303BMJ only).



303VS/303BMJ Single Lift Slider NAFS, R-PG50, Water 360 pa, Air - A3, F10 NFRC Certified **AAMA Certified CSA Certified**

303VS/303BMJEV Double Lift End Vent Slider
For rating and certification information, including ENERGY STAR qualified window performance packages please visit our web site at: www.vinylwindowdesigns.com

Single Lift Out Slider 303VS/303BMJ

Width: 18" to 72" Height: 12" to 50"

Note: If Height is between 12" and 13" Width can be no less than 22"

If Height is 13" or more Width minimum is 18"

Maximum size with Triple Glass or Keepsafe™ is 18 sq. ft.

Double End Vent 303VSEV/303BMJEV

Width: 42" to 120" Height: 12" to 50"

Widths over 108" to 120" are only available 1/4 1/2 1/4 Widths less than 56" must be 1/3 1/3 1/3 1/3

Maximum size with Triple Glass or Keepsafe™ is 25 sq. ft.

lass Double Bond Glazing System

Flexible dual durometer seals hug the sash glass from both sides. The system also includes a glazing tape applied to the interior side. The result is an unprecedented barrier against air and water penetration.

· Commercial Glazing Technique

Exterior glass stops, combined with the Double Bond Glazing, are more effective in maintaining a well-sealed window.

High Performance Glass Options

Choose Solar Gain Low E for free solar heat or Solar Shield Low E for reducing solar heat gain. Argon and Krypton Gas fillings will maximize heat savings! KeepSafe Glass is the laminate of choice for security, quiet and safety! E-Clean Glass uses the energy of the sun to reduce dirt on your glass.

Warm Edge Spacer Technology

Only the best warm edge spacers will reduce perimeter condensation on an insulating glass unit, fight mold and increase the comfort of your home.

IGMA Approved

Certification Numbers - Stainless #2521-P, TempSmartTM #2248

7/8" Overall Insulating Glass

Results in superior thermal performance. Our optional high performance triple glass, with Krypton Gas and double Solar Shield Low E, results in a R8.2 (.12U) center glass value



• Triple Seal

Three layers of premium Fin Seal stop air and water as they reduce sound transmission. Benefit from the best sliding seals available!

Double Neoprene Bulbs

Compression style seals close tight where the sash meets the frame and sliding is not required. Our engineers insisted that you get this premium component!

Recessed Tilt Latches

Your operating sash is designed for easy removal when cleaning. Pull down the top tilt style latches and lift out

Heavy duty 180 degree locking cams pull your operating sash and frame tightly together for a great seal!


Hinged Drain Covers

Designed to keep bugs out while allowing water to flow to the outside.

















-









As we are constantly improving our products, specifications may have changed from those herein. Please contact VWD regarding up-to-date specifications



Authorized Distributor













